


**IGBT in advanced TrenchFS Technology with soft and fast recovery anti-parallel diode**  
具有先进 TrenchFS 技术的 IGBT 且反并联软快恢复二极管

### Features:

#### 特性

- TrenchFS technology  
沟槽栅场终止技术
- Low conduction and switching losses  
低导通和开关损耗
- Positive temperature coefficient  
饱和电压正温度系数
- Short Circuit withstand time-5 $\mu$ s  
具备5 $\mu$ s短路承受能力



### Applications:

#### 应用

- Automobile motor drives  
汽车电机驱动

Type 型号	$V_{CE}$ [V] 集电极-发射极电压	$I_C$ [A] 集电极电流	$V_{CEsat}$ [V] 饱和电压	$T_{jmax}$ [°C] 最高结温	Marking 标记	Package 封装
BGM160T75SD	750	160	1.6	175	160T75SD	TO247Plus



## Maximum Rated Values

### 最大额定参数

Parameter 参数	Symbol 符号	Value 值	Unit 单位
Collector-emitter voltage, $T_j \geq 25^\circ\text{C}$ 集电极-发射极电压, $T_j \geq 25^\circ\text{C}$	$V_{CE}$	750	V
Collector current, $T_c = 25^\circ\text{C}$ 集电极电流, $T_c = 25^\circ\text{C}$	$I_C$	320	A
Collector current, $T_c = 100^\circ\text{C}$ 集电极电流, $T_c = 100^\circ\text{C}$	$I_C$	160	
Pulsed collector current, $t_p$ limited by $T_{j\max}$ 集电极脉冲电流, 脉宽时间受 $T_{j\max}$ 限制	$I_{Cpuls}$	320	
Diode forward current, $T_c = 25^\circ\text{C}$ 二极管正向电流, $T_c = 25^\circ\text{C}$	$I_F$	320	
Diode forward current, $T_c = 100^\circ\text{C}$ 二极管正向电流, $T_c = 100^\circ\text{C}$	$I_F$	160	
Diode pulsed current 二极管脉冲电流	$I_{Fpuls}$	640	
Gate-emitter voltage 栅极-发射极电压	$V_{GE}$	$\pm 20$	V
Short Circuit withstand time $V_{GE} = 15\text{V}, V_{CC} \leq 400\text{V}, T_j \leq 150^\circ\text{C}$ 短路耐受时间	$t_{sc}$	5	us
Total power dissipation, $T_c = 25^\circ\text{C}$ 总耗散功率, $T_c = 25^\circ\text{C}$	$P_{tot}$	833	W
Operating junction temperature 最高结温	$T_{j\max}$	175	°C
Operating junction temperature 工作结温	$T_{jop}$	-40...+150	
Storage temperature 储存温度	$T_{stg}$	-55...+150	
Soldering temperature, 1.6mm from case for 10s 焊接温度	$T_{st}$	260	



**Thermal Resistance**

**热阻**

Parameter 参数	Symbol 符号	Value 值	Unit 单位
IGBT Thermal resistance junction to case IGBT 结-管壳热阻	$R_{th(j-c)}$	0.18	$^{\circ}C/W$
Diode Thermal resistance junction to case 二极管结-管壳热阻	$R_{th(j-c)}$	0.30	$^{\circ}C/W$
Thermal resistance junction to ambient 结-环境热阻	$R_{th(j-a)}$	40	$^{\circ}C/W$

**Electrical Characteristic at  $T_j = 25^{\circ}C$  (unless otherwise specified)**

**$T_j=25^{\circ}C$ 时电学特性（除非特别声明）**

Parameter 参数	Symbol 符号	Conditions 条件	Value 值			Unit 单位
			Min. 最小值	Typ. 典型值	Max. 最大值	

**Static Characteristic**

**静态特性**

Collector-emitter breakdown voltage 集电极-发射极击穿电压	$V_{(BR)CES}$	$V_{GE}=0V,$ $I_C=100\mu A$	750	-	-	V	
Collector-emitter saturation voltage 集电极-发射极饱和电压	$V_{cesat}$	$V_{GE}=15V,$ $I_C=160A$	$T_j=25^{\circ}C$	-	1.6		2.0
			$T_j=150^{\circ}C$	-	2.0		-
Diode forward voltage 二极管正向电压	VF	$V_{GE}=0V,$ $I_F=160A$	$T_j=25^{\circ}C$	-	1.8		2.4
			$T_j=150^{\circ}C$	-	1.9		-
Gate-emitter threshold voltage 栅极-发射极阈值电压	$V_{GE(th)}$	$I_C=3mA,$ $V_{CE}=V_{GE}$	5.0	6.0	7.0		
Collector-emitter cut-off current 集电极-发射极截止电流	$I_{CES}$	$V_{CE}=750V,$ $V_{GE}=0V$	-	-	100	$\mu A$	
Gate-emitter leakage current 栅极-发射极漏电流	$I_{GES}$	$V_{CE}=0V,$ $V_{GE}=\pm 20V$	-200	-	200	nA	

**Dynamic Characteristic**

**动态特性**

Input capacitance 输入电容	$C_{ies}$	$V_{CE}=25V,$ $V_{GE}=0V,$ $f=1MHz$	-	8750	-	pF
Output capacitance 输出电容	$C_{oes}$		-	670	-	
Reverse transfer capacitance 反向传输电容	$C_{res}$		-	110	-	



Gate charge 门极电量	$Q_G$	$V_{CC}=400V, I_C=160A,$ $V_{GE}=15V$	-	270	-	nC
Short circuit current 短路电流	$I_{C(sc)}$	$V_{CC}=400V, V_{GE}=15V,$ $tpsc \leq 5\mu s, T_j=150^\circ C$	-	770	-	A

## Switching Characteristic at $T_j=25^\circ C$ (Inductive Load)

$T_j=25^\circ C$ 时开关特性（感性负载）

Parameter 参数	Symbol 符号	Conditions 条件	Value 值			Unit 单位
			Min. 最小值	Typ. 典型值	Max. 最大值	
<b>IGBT Characteristic</b> IGBT 特性						
Turn-on delay time 开通延迟时间	$t_{d(on)}$	$T_j=25^\circ C,$ $V_{CC}=400V,$ $I_C=160A,$ $V_{GE}=7.5/15V,$ $R_G=4.7\Omega,$ Energy losses include "tail" and diode reverse recovery.	-	132	-	ns
Rise time 上升时间	$t_r$		-	89	-	
Turn-off delay time 关断延迟时间	$t_{d(off)}$		-	223	-	
Fall time 下降时间	$t_f$		-	108	-	
Turn-on energy 开通损耗	$E_{on}$		-	8.97	-	mJ
Turn-off energy 关断损耗	$E_{off}$		-	5.95	-	
Total switching energy 总开关损耗	$E_{ts}$	-	14.92	-		

## Anti-Parallel Diode Characteristic

反并联二极管特性

Reverse recovery time 反向恢复时间	$t_{rr}$	$T_j=25^\circ C,$ $V_R=400V,$ $I_F=160A,$ $diF/dt=1500A/\mu s$	-	195	-	ns
Recovered charge 恢复电荷	$Q_r$		-	6.5	-	$\mu C$
Peak reverse recovery current 反向恢复峰值电流	$I_{RM}$		-	65	-	A
Reverse recovered energy 反向恢复损耗	$E_{rec}$		-	1.2	-	mJ



## Switching Characteristic at $T_j=150^\circ\text{C}$ (Inductive Load)

### $T_j=150^\circ\text{C}$ 时开关特性（感性负载）

Parameter 参数	Symbol 符号	Conditions 条件	Value 值			Unit 单位
			Min. 最小值	Typ. 典型值	Max. 最大值	
<b>IGBT Characteristic</b>						
<b>IGBT 特性</b>						
Turn-on delay time 开通延迟时间	$t_{d(on)}$	$T_j=150^\circ\text{C}$ , $V_{CC}=400\text{V}$ , $I_C=160\text{A}$ , $V_{GE}=-7.5/15\text{V}$ , $R_G=4.7\Omega$ , Energy losses include “tail” and diode reverse recovery.	-	182	-	ns
Rise time 上升时间	$t_r$		-	348	-	
Turn-off delay time 关断延迟时间	$t_{d(off)}$		-	198	-	
Fall time 下降时间	$t_f$		-	152	-	
Turn-on energy 开通损耗	$E_{on}$		-	13.88	-	mJ
Turn-off energy 关断损耗	$E_{off}$		-	9.22	-	
Total switching energy 总开关损耗	$E_{ts}$		-	23.1	-	

## Anti-Parallel Diode Characteristic

### 反并联二极管特性

Reverse recovery time 反向恢复时间	$t_{rr}$	$T_j=150^\circ\text{C}$ , $V_R=400\text{V}$ , $I_F=160\text{A}$ , $diF/dt=1500\text{A}/\mu\text{s}$	-	315	-	ns
Recovered charge 恢复电荷	$Q_r$		-	13	-	$\mu\text{C}$
Peak reverse recovery current 反向恢复峰值电流	$I_{RM}$		-	80	-	A
Reverse recovered energy 反向恢复损耗	$E_{rec}$		-	2.5	-	mJ

## ELECTRICAL CHARACTERISTICS

### 特性曲线




Figure 1. Typical output characteristic( $T_j=25^{\circ}\text{C}$ )




Figure 2. Typical output characteristic( $T_j=150^{\circ}\text{C}$ )




Figure 3. Typical collector-emitter saturation voltage Characteristic( $V_{GE}=15\text{V}$ )




Figure 4. Typical transfer voltage( $V_{CE}=20\text{V}$ )




Figure 5. Saturation Voltage vs.  $V_{GE}$ ( $T_j=25^{\circ}\text{C}$ )




Figure 6. Saturation Voltage vs.  $V_{GE}$ ( $T_j=175^{\circ}\text{C}$ )




Figure 7. Forward Characteristics




Figure 8. Turn Off Switching SOA Characteristics




Figure 9. Typical switching time VS  $V_{ce}$   
( $T_j=150^\circ\text{C}, V_{ce}=400\text{V}, V_{GE}=15\text{V}, I_c=160\text{A}, R_G=4.7\ \Omega$ )




Figure 10. Typical switching times VS  $I_c$   
( $T_j=150^\circ\text{C}, V_{ce}=400\text{V}, V_{GE}=15\text{V}, R_G=4.7\ \Omega$ )




Figure 11. Typical switching energy losses VS  $I_c$   
( $T_j=150^\circ\text{C}, V_{ce}=400\text{V}, V_{GE}=15\text{V}, R_G=4.7\ \Omega$ )







Figure 12. Typical switching energy losses VS  $V_{ce}$   
( $T_j=150^\circ\text{C}, V_{GE}=15\text{V}, I_c=160\text{A}, R_G=4.7\ \Omega$ )



**Figure 13. BVCES VS Tj (Ic=1mA)**



**Figure 14. Transient Thermal Impedance of IGBT**




**Figure 15. Transient Thermal Impedance of Diode**





TO247Plus Outline Dimensions:

TO247Plus 外形尺寸



Packing

包装

Packing	pcs/tube	tube/ inner box	inner box/ carton	pcs/carton
Tube	30	12	6	2160

## RESTRICTIONS ON PRODUCT USE

- The information contained herein is subject to change without notice.
- **BYD Semiconductor Company Limited** exerts the greatest possible effort to ensure high quality and reliability. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing products, to comply with the standards of safety in making a safe design for the entire system, including redundancy, fire-prevention measures, and malfunction prevention, to prevent any accidents, fires, or community damage that may ensue. In developing your designs, please ensure that products are used within specified operating ranges as set forth in the most recent products specifications.
- The products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury (“Unintended Usage”). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of products listed in this document shall be made at the customer’s own risk.